

# Specifications

Photo is representative

## Eaton DH361UWK

Eaton heavy duty single-throw non-fused safety switch, Single-throw, 30 A, NEMA 4X, Stainless steel, Non-Fusible, 3-pole, Three-wire, 7.5 at 480 Vac TD 1 Ph, 10 at 600 Vac TD 1 Ph, 10 at 240 Vac TD 3 Ph, 20 at 480 Vac TD 3 Ph

### General specifications

<b>PRODUCT NAME</b>	Eaton heavy duty non-fusible safety switch
<b>CATALOG NUMBER</b>	DH361UWK
<b>UPC</b>	782113205724
<b>PRODUCT LENGTH/DEPTH</b>	10.22 in
<b>PRODUCT HEIGHT</b>	14.14 in
<b>PRODUCT WIDTH</b>	8.76 in
<b>PRODUCT WEIGHT</b>	17 lb
<b>WARRANTY</b>	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
<b>COMPLIANCES</b>	NEC 230.62 (C) Compliant Barrier
<b>CERTIFICATIONS</b>	UL Listed
<b>CATALOG NOTES</b>	Suitable for service entrance use with a neutral or ground lug kit installed
<b>PRODUCT TYPE</b>	Non-fusible safety switch



Powering Business Worldwide

## Physical Attributes

<b>ENCLOSURE</b>	NEMA 4X
<b>ENCLOSURE MATERIAL</b>	Stainless steel
<b>FUSE CONFIGURATION</b>	Non-fusible
<b>NUMBER OF POLES</b>	Three-pole
<b>NUMBER OF WIRES</b>	3
<b>TYPE</b>	Single-throw

## Miscellaneous

<b>PRODUCT CATEGORY</b>	Heavy Duty, Non-Fusible
-------------------------	-------------------------

## Performance Ratings

<b>AMPERAGE RATING</b>	30A
<b>HP RATING - MAX</b>	7.5 at 480 Vac TD 1 Ph, 10 at 600 Vac TD 1 Ph, 10 at 240 Vac TD 3 Ph, 20 at 480 Vac TD 3 Ph, 30 at 600 Vac TD 3 Ph, 5 at 250 Vdc
<b>NEMA RATING</b>	NEMA 4X
<b>VOLTAGE RATING</b>	600 V

## Resources

CATALOGS	<a href="#">Commercial Distribution, Switching Devices, Volume 2, Tab 1</a>
SPECIFICATIONS AND DATASHEETS	<a href="#">Eaton Specification Sheet - DH361UWK</a>

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



**Eaton Corporation plc** Eaton House  
30 Pembroke Road  
Dublin 4, Ireland  
Eaton.com

Follow us on social media to get the latest product and support information.

