

Electronic Cable



Unshielded Electronic Cable Riser / CMR, CL3R, FPLR

Part Number	Description	Weight (Nom.)	Outside Dia. (Nom.)
53101	22/2 stranded BC (7/30)	7 lbs	0.110"
53112	22/4 stranded BC (7/30)	13 lbs	0.127"
51116	22/6 stranded BC (7/30)	19 lbs	0.161"
51118	22/8 stranded BC (7/30)	24 lbs	0.174"
51120	22/10 stranded BC (7/30)	32 lbs	0.202"
51122	22/12 stranded BC (7/30)	35 lbs	0.209"
51104	18/2 stranded BC (7/0.0152)	15 lbs	0.142"
51114	18/4 stranded BC (7/0.0152)	27 lbs	0.166"
51117	18/6 stranded BC (7/0.0152)	41 lbs	0.215"
51119	18/8 stranded BC (7/0.0152)	54 lbs	0.233"
51123	18/12 stranded BC (7/0.0152)	78 lbs	0.275"
51105	16/2 stranded BC (19/0.0117)	23 lbs	0.168"
51115	16/4 stranded BC (19/0.0117)	43 lbs	0.203"
51140	14/2 stranded BC (19/0.0147)	35 lbs	0.206"
51174	14/4 stranded BC (19/0.0147)	65 lbs	0.252"
51142	12/2 stranded BC (19/0.0185)	53 lbs	0.260"



Overall Shield Electronic Cable Riser / CMR, CL3R, FPLR

Part Number	Description	Weight (Nom.)	Outside Dia. (Nom.)
95211	22/2 stranded BC (7/30) OAS	10 lbs	0.129"
67001	22/4 stranded BC (7/30) OAS	16 lbs	0.148"
67005	22/6 stranded BC (7/30) OAS	23 lbs	0.178"
67007	22/8 stranded BC (7/30) OAS	29 lbs	0.192"
67009	22/12 stranded BC (7/30) OAS	41 lbs	0.230"
95214	18/2 stranded BC (7/0.0152) OAS	18 lbs	0.163"
67003	18/4 stranded BC (7/0.0152) OAS	34 lbs	0.193"
67006	18/6 stranded BC (7/0.0152) OAS	46 lbs	0.230"
67008	18/8 stranded BC (7/0.0152) OAS	59 lbs	0.249"
67010	18/12 stranded BC (7/0.0152) OAS	86 lbs	0.301"
95215	16/2 stranded BC (19/0.0117) OAS	26 lbs	0.187"
95230	16/4 stranded BC (19/0.0117) OAS	46 lbs	0.218"
95253	14/2 stranded BC (19/0.0147) OAS	37 lbs	0.216"



Each Pair Shielded Electronic Cable

Part Number	Description	UL Type	Weight (Nom.)	Outside Dia. (Nom.)
77304	22/2pr stranded BC (7/30) EPS	CMP / CL3P	24 lbs	0.190"
77306	22/3pr stranded BC (7/30) EPS	CMP / CL3P	37 lbs	0.229"
95510	18/2pr stranded BC (7/0.0152) EPS	CMR / CL3R	40 lbs	0.302"
95900	22/2pr stranded BC (7/30) EPS	CMR / CL3R	21 lbs	0.189"
95501	22/3pr stranded BC (7/30) EPS	CMR / CL3R	32 lbs	0.255"
95220	22/4 stranded BC (7/30) 2 cond OAS	CMR / CL3R	19 lbs	0.179"

Unshielded Electronic Cable Plenum / CMP, CL3P, FPLP

Part Number	Description	Weight (Nom.)	Outside Dia. (Nom.)
72302	22/2 stranded BC (7/30)	10 lbs	0.109"
72304	22/4 stranded BC (7/30)	15 lbs	0.127"
72306	22/6 stranded BC (7/30)	22 lbs	0.150"
72308	22/8 stranded BC (7/30)	27 lbs	0.163"
72310	22/10 stranded BC (7/30)	37 lbs	0.198"
72312	22/12 stranded BC (7/30)	43 lbs	0.203"
71902	18/2 stranded BC (7/0.0152)	20 lbs	0.142"
71904	18/4 stranded BC (7/0.0152)	33 lbs	0.166"
71906	18/6 stranded BC (7/0.0152)	48 lbs	0.205"
71908	18/8 stranded BC (7/0.0152)	61 lbs	0.223"
71910	18/10 stranded BC (7/0.0152)	75 lbs	0.262"
71912	18/12 stranded BC (7/0.0152)	88 lbs	0.271"
71702	16/2 stranded BC (19/0.0117)	27 lbs	0.177"
71704	16/4 stranded BC (19/0.0117)	51 lbs	0.214"
71502	14/2 stranded BC (19/0.0147)	41 lbs	0.206"

Overall Shield Electronic Cable Plenum / CMP, CL3P, FPLP

Part Number	Description	Weight (Nom.)	Outside Dia. (Nom.)
75302	22/2 stranded BC (7/30) OAS	11 lbs	0.128"
75304	22/4 stranded BC (7/30) OAS	17 lbs	0.146"
75306	22/6 stranded BC (7/30) OAS	23 lbs	0.172"
75308	22/8 stranded BC (7/30) OAS	30 lbs	0.190"
75902	18/2 stranded BC (7/0.0152) OAS	19 lbs	0.162"
75904	18/4 stranded BC (7/0.0152) OAS	32 lbs	0.186"
75906	18/6 stranded BC (7/0.0152) OAS	47 lbs	0.227"
75908	18/8 stranded BC (7/0.0152) OAS	60 lbs	0.246"
75702	16/2 stranded BC (19/0.0117) OAS	26 lbs	0.187"
75704	16/4 stranded BC (19/0.0117) OAS	48 lbs	0.224"
75502	14/2 stranded BC (19/0.0147) OAS	39 lbs	0.216"